

## Specification

<b>Display Type:</b>	LCD with LED Backlight	<b>Certifications</b>	TUV / FCC Class B
<b>Display Resolution</b>	1920 x 1080 FHD	<b>Weight:</b>	64lbs, 29Kg
<b>Module Size:</b>		55"	51.8lbs, 23.5Kg
55"	47.95 x 3.49 x 26.94 inches (1218 x 88.7 x 684.2mm)	<b>Shipping Weight:</b>	
47"	41.31 x 3.29 x 23.24 inches (1049.2 x 83.7 x 590.2mm)	55"	83.5lbs, 38Kg
<b>Bezel Size</b>	2.65mm each side (average)	47"	67.2lbs, 30.5Kg
<b>Brightness</b>	500Nit (cd/m <sup>2</sup> ) or 800Nit (cd/m <sup>2</sup> )	<b>Shipping Carton Size</b>	1346 x 254 x 838mm
<b>Contrast</b>	4000:1	<b>Handling</b>	53" x 10" x 33"
<b>Color</b>	1.06 Billion ( 10 Bit )	<b>Mounting System</b>	4 handles per Video Wall Module Supports industry standard VESA mount systems
<b>Viewing Angle</b>	89/89/89/89°	<b>Options</b>	(Chief LSMVU, Peerless etc.) DVI, VGA, HD-SDI, Fiber inputs Dual redundant power supplies Ethernet based status monitoring Spectractal calibration compatibility
<b>Orientation</b>	Landscape / Portrait / Other	<b>Video-Wall Processor</b>	Compatible with all major brands
<b>Video Inputs</b>	DVI / HDMI input	<b>Security</b>	Kensington Lock Slot
<b>Video Wall Configurations</b>	Any matrix configuration		
<b>IR Control Module</b>	Controls display settings		
<b>Power Consumption</b>	500Nit : 205W / 800Nit : 216W		
<b>Operation</b>	Designed for 24/7/365 operation		
<b>Warranty</b>	3 years		

Specifications subject to change without notice